

Avery Dennison® Monarch® Pathfinder® 6057 Printer

SCAN, PRINT AND APPLY - IT'S THAT SIMPLE

The Avery Dennison® Monarch® Pathfinder® 6057 printer combines scanning, printing and applying processes into a unique one-piece handheld solution for faster markdowns and promotional labeling at retail, or inventory management within manufacturing and distribution.

RETAIL APPLICATIONS

With up to 35% of apparel unit volume moving at discounted pricing, promotional pricing matters. Using the Pathfinder 6057, associates are able to perform markdown and promotional labeling with greater speed and accuracy than conventional red-pen techniques.

- Pricing events are streamlined and completed on-time, the first time, with less associate handling
- Faster and more accurate than using "red pens," mechanical price labelers or portable "belt printers"
- Improved accuracy ensures the ticket price is the price paid at checkout, ensuring a positive customer experience
- More efficient pricing means more time for your staff to serve customers

MANUFACTURING AND DISTRIBUTION CENTER APPLICATIONS

The Pathfinder 6057 is an intelligent one-piece inventory management tool that allows users to quickly and accurately capture data, cross-dock, route, date code and perform compliance labeling, all of which can help reduce labor costs.

The unique scan, print and apply feature of the Pathfinder 6057 out performs competitor two-piece printer and data collections solutions.* Because bar code scanning, labeling, printing and applying can be performed with just one hand, employees are able to spend less time handling items, increasing labeling speed and accuracy.

ELEVATING BRANDS. ACCELERATING PERFORMANCE.

For more information call: 800.543.6650, prompt 5 or email: printersolutions@averydennison.com



Innovative, intelligent and sustainable labeling and printing solutions that accelerate supply chain performance, increase productivity and elevate the consumer experience.

*Based on results from internal time studies

Avery Dennison® Monarch® Pathfinder® 6057 Printer



SPECIFICATIONS

DIMENSIONS

Height - 9.84" (250 mm) Width - 8.25" (209 mm)
Depth - 3.00" (76 mm) Weight - 1.94 lbs (0.88 kg)
Shipping Wt. - 5.5 lbs (2.52 kg)

PRINTING METHOD

Thermal Direct

KEYPAD/DISPLAY

Virtual keyboard on display. Three software controlled contextual keys, off/on, trigger, 1/2 VGA (320x480 pixel) VGA color graphics LCD with touchscreen.

MEMORY

128 MB RAM, 256 MB Flash
Standard Micro SD memory card

COMMUNICATIONS

USB port
Optional 802.11 a/b/g/n dual band

BAR CODE TYPES

UPCA +2/+5, UPCE +2/+5, EAN8 +2/+5, EAN13 +2/+5, Interleaved, 2 of 5, Code 16k, Codabar (NW7), Code 128, Code 39, MSI, PDF417, Code 93, Postnet, Maxicode, QR Code, GS1 databar, Datamatrix and RSS.

STANDARD FONTS

TrueType® and International

FONT MAGNIFICATION

4 to 200 pt. for scalable/TrueType® fonts

PRINTER WARRANTY

One (1) year parts and labor (ship-in).
Full written warranty statement is available on request.

PRINTHEAD WARRANTY

Six (6) months, or one million inches (1,000,000"), whichever occurs first.

SUPPLIES

The printer supports butt cut, die cut and continuous supplies.

SUPPLY TYPES

Tags, labels and receipt paper

SUPPLY SIZES

Width - 1.1" up to 2.0" (28 mm to 51 mm)
Length - 0.55" to 8.0" (14 mm to 203 mm)
Supply Roll Lengths - 420" to 580" (10.7 to 14.7 meters)
Custom lengths are available
Minimum apply is 0.785" (19mm)

SUPPLY THICKNESS

Tags - 7 mils (0.18mm)
Labels - 2.4 mils (0.061mm)

MAXIMUM PRINT AREA

1.89" x 7.94" (48 mm x 201.7 mm)

SENSING

Black mark only
Integrated on-demand sensor

ENVIRONMENTAL RANGES

Operating Temperature - 41° to 104° F (5° to 40° C)
Storage - -4° to 122° F (-20° to 50° C)
Humidity/Operating and Storage - 5% to 90% non-condensing

ELECTROSTATIC DISCHARGE AND AIR QUALITY

Some issues with electronic equipment may occur in environments prone to static discharge or extreme dust conditions. Avery Dennison suggests that you take precautions to minimize these issues.

PERFORMANCE

Power Source - 7.4V Lithium Ion battery pack
Print Speed - Up to 5 ips (127 mm/sec)

REWINDER

For label printing that remains in strips and not cut / stacked
5% to 90%, non-condensing Electrostatic Discharge and Air.

SCANNER

Integrated 2D or 1D scanner

PRINT RATIO

30% black maximum per square inch

INCHES PER CHARGE

Up to 3,000" (76 meters) of 30% black printing on the supply.
Factors such as scanning, use of LAN radios and duty cycle can reduce inches printed per charge.

BATTERY CYCLE LIFE

Approximately 300 full discharge cycles. Many factors affect individual battery performance.

RECOMMENDED DUTY CYCLE

33% duty cycle for continuous printing (5 minutes out of 15-minute time intervals). On demand or intermittent printing has no restrictions.

OPTIONS

- 802.11 a/b/g/n dual band
- Integrated 2D or 1D scanner

ACCESSORIES

- Battery (part#12009502) 9465™ four-station battery charger
- 9462™ single station battery charger
- Deluxe hand strap (part#130606)
- USB cable
- 6055/6054 communication/charging/docking station
- Shoulder strap (part#130605)
- Deluxe padded wrist strap (part#130604)



AMERICAS

170 Monarch Lane
Miamisburg, OH 45342
937 865 2123 (direct)
Tel +800 543 6650
(8:00 a.m.–6:30 p.m., EDT)
Fax +937 865 6663

ASIA

No. 7 Chun Ying Street
Tseung Kwan O Industrial
Estate
New Territories, Hong Kong
Tel +852 2372 3169
Fax +852 2995 0014

WESTERN EUROPE

1 Thomas Road
Wooburn Green
Bucks HP10 0PE
Tel +(44) 1628 859500
Fax +(44) 1628 859567

ASIA PACIFIC

NEW SOUTH WA

61 Vore Street
Silverwater NSW 2128
Tel +(02) 9647 1833
Fax +(02) 9647 1914
Toll free (Outside Sydney only)

Accelerating supply chain
performance and elevating
the consumer experience.

VERY DENNISON® SERVICE AND SUPPORT

Our technical specialists and service representatives can provide installation support, training and operating recommendations. For more information call 800.543.6650, option 7.