# Avery Dennison® Monarch® 9419 Printer



# **TABLETOP PERFORMANCE, DESKTOP SIZE**

Bringing together the full functionality of a large thermal printer and space-saving convenience and cost efficiency of a traditional desktop printer, the Avery Dennison Monarch® 9419 Printer is designed for an array of in-store retail printing needs, including:

- Shelf and markdown labels for easy customer price recognition
- Durable shipping labels for store transfers or customer purchases
- Reticketing that looks and feels like source tagging

The 9419 also has an integrated, user-positionable 3.5" color display – one of the largest display of any desktop printer on the market. Also included is the real-time clock and a label peel mechanism with present sensor as standard.

Durable construction makes it a great choice for manufacturing and distribution center labeling applications.

# **READY-TO-USE OUT OF THE BOX**

As soon as you remove the Avery Dennison Monarch® 9419 printer from its box and follow the easy setup instructions, you'll be printing and labeling in no time! It comes pre-loaded with popular in-store label formats for price tags, shelf labels, and shipping labels, or just download your preferred formats from your host. For standalone printing, simply add a keyboard or scanner.

Whether your store has little or no IT support or you just want a faster way to implement price changes, the 9419 is the optimal solution with a powerful performance and a compact size.

# SUSTAINABLE LABELING

Reduced Energy Consumption - ENERGY STAR® certifed\*

Avery Dennison® EcoCapacity+™ Supplies

- 30% more labels per roll
- 35% fewer roll changes

# **ELEVATING BRANDS. ACCELERATING PERFORMANCE.**

For more information call: 800.543.6650, prompt 5 or email: printersolutions@averydennison.com





Innovative, intelligent and sustainable labeling and printing solutions that accelerate supply chain performance, increase productivity and elevate the consumer experience.

# **Avery Dennison®** Monarch® 9419 **Printer**



## **SPECIFICATIONS**

#### **DIMENSIONS**

10" (254 mm) display upright 7.8"(198mm) display down

DEPTH SHIPPING WEIGHT

#### PRINTING

PRINTING METHOD

PRINT HEAD WIDTH 4.25" (108mm) for 203 dpi

4.17" (106mm) for 300 dpi PRINT HEAD RESOLUTION

203dpi (8 dots/mm) or 300dpi (12 dots /mm)

# MEMORY

128 MR DDR2 RAM 128 MB FLASH

## **BARCODES**

One-dimensional - Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E,Code 39, Code 93, Code128UCC, Code128 subsets A.B.C, EAN and UPC 2(5) digits add-on, MSI, POSTNET, EAN14, One-dimensional (Offline only) PLESSEY, China Post, ITF14, Code 11, TELEPEN, TELEPENN,
PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS, Two-dimensional - PDF-417, Maxicode, DataMatrix, QR code, Two-dimensional (Offline only) - Azteo,TLC39,CODABLOCK F mode,Micro PDF 417, GS1 DataBar (RSS barcode)

# COMMUNICATIONS

USB 2.0 Device (Type B connector) USB 2.0 Host (Type A Connector) IEEE 802.3 Ethernet, 10/100 Mbps (RJ45 connector) Optional: 802.11 a/b/g/n dual band wireless (North America, EU, and Australia only) RS232C 9-pin serial interface

# KEYPAD / DISPLAY

6-button keypad control 3.5" Thin Film Transistor LCD (128W x 64H dots)

# PRINTER CONTROL LANGUAGES

# **FONTS**

Internal Monotype Imaging® true type font engine with one CG Triumvirate Bold Condensed scalable font Fonts can also be downloaded to the printer

# **SUPPLIES**

#### MEDIA SENSING METHOD

Movable combined sensor for Die Cut and Black Mark

center-hissed

#### SUPPLY TYPES

Tags and Adhesive Labels (Paper or Synthetic) in roll or fanfold format Perforated or continuous supply

## SUPPLY SIZES

Width: 0.75" ~ 4.4" (19~112 mm)

Width (with Peel): 0.75" ~ 4.4" (19~112mm) Length: 203dpi: 0.1" ~ 1,000" (3 ~ 25,400mm) 300dpi: 0.1" ~ 450" (3 ~ 11,430mm) Length: (peel mode): 1" ~ 6"" (25mm ~ 152 mm)

## MAX ROLL DIAMETER

5" (127mm) OD on a 1"- 1.5" (25-38mm) core

## SUPPLY THICKNESS

4.25"" X 10.0"" (108mm x 254mm) with 203 dpi 1.77\*\* x 10.0\*\* (106mm x 254mm) with 300 dpi Larger images (up to 29" (75 cm) in length) can be printed using continuous supply and reallocating memory

#### RIBBON I FNGTH

300 Meters (11,811"), ink coated outside, max. 67 mm OD

# **ENVIRONMENTAL RANGES**

#### OPERATING TEMPERATURE/HUMIDITY 5 ~40°C, 25 ~ 85% non-condensing for thermal direct operation

5 ~ 35°C, 25 ~ 85% non-condensing for thermal transfer operation

# STORAGE/HUMIDITY

-40 ~ 60°C, 10 ~ 90% non-condensing

# PERFORMANCE

External universal switching power supply Input: AC 100-240V, 2.5A, 50-60Hz Output: DC 24V, 3,75A, 90W Power Consumption: 2.9 Amps

- Max. print speed 8 ips (203mm/s)
- Max. print speed for 300 dpi 6 ips (152/mm/s)

# **OPTIONS AND ACCESSORIES**

- Keyboard
- Cutter
- OS Bluetooth\*
- Wireless networking
- Additional memory via SD card
- External supply holder

Accelerating supply chain performance and elevating the consumer experience.

# **AVERY DENNISON® SERVICE AND SUPPORT**

Our technical specialists and service representatives can provide installation support, training and operating recommendations.

ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.

ENERGY STAR products are third-party certified by an EPA-recognized Certification Body.

The information contained herein is believed to be reliable but Avery Dennison makes no representations concerning the accuracy or correctness of the data. This product, like any other should be tested by the customer/user thoroughly under end user conditions to ensure the product meets the particular requirements. Independent results may vary. Avery Dennison and the logo are registered trademarks of Avery Dennison Corp. Third party trademarks and/or trade names used herein are the property of their respective owner(s). ©2017 Avery Dennison Corporation, All Rights Reserved