

XPU PALLET LABELING UNIT

SPECIFICATIONS		XPU	
capacity		180 pallets per hour*	
labels	label material	self-adhesive paper labels, optional PE/PP	
	label roll	outer Ø: up to 300 mm, inner Ø: 76 mm or 102 mm	
	label size	A5 portrait (148 x 210 mm)	
hardware	print- & apply system	NOVEXX Solutions ALX 926 RH, applicator with rotating head for front and side application of labels	
	machine control	control cabinet incl. power supply	
		Siemens PLC	
		signal relays	
		operator interface	
emergency stop			
control light	visual light indication of machine status (red, orange, green)		
options		scanner for barcode readability	
		applicator for PE/PP label material	
		home switch for applicator head protection	
		3-side pallet labeling	
		swing out module for ALX	
		RFID module	
dimensions/ surroundings		software for label design and data management	
	height	2045 up to 2535 mm	
	width	860 mm	
	length	1300 mm	
	weight	200 kg	
	power	230 V – AC, 10 A	
	operating temperature	10–35 °C	
	air pressure	6 bar, 50 l/min	
	directives		2006/42/EC machine guideline
			2007/DS/EN ISO 13849-1 safe operating systems
		2014/35/EU low-voltage directive	
		2014/30/EU EMC directive	

* with 2 labels per pallet, excl. pallet transport

The information contained herein is believed to be reliable but NOVEXX Solutions makes no representations concerning the accuracy or correctness of the data. The information, like any other should be confirmed independently for the particular end user conditions to ensure the proposed labeling meets the relevant requirements and regulations. © 2017 Novexx Solutions GmbH, All Rights Reserved. Third party trademarks and/or trade names may be used herein are the property of their respective owner(s).